

SATA III (6Gbps) 2-port PCI-Express Controller Card

User Manual

Ver. 1.00

All brand names and trademarks are properties of their respective owners

Features

- Compliant with PCI-Express Specification v2.0 and backward compatible with PCI-Express 1.x
- Compliance Serial ATA AHCI Spec.Rev.1.3, Serial ATA Revision 3.0
- Hot plug and Hot Swap
- Supports communication speeds of 6.0 Gbps, 3.0 Gbps, and 1.5 Gbps
- Supports 2 ports Serial ATA
- Supports Native Command Queue (NCQ)
- Supports Port Multiplier

Package Contents

- 1 x User Manual
- 1 x SATA III (6Gbps) 2-port PCI-Express Controller Card
- 1 x SATA Cable
- 1 x Driver CD
- PS: eSATA Card Without SATA Cable

System Requirements

Windows® 7 (32 / 64 bit) / Vista / Server 2003 / XP / 2000

Hardware Installation

1. Turn off the power to your computer
2. Unplug the power cord and remove your computer's cover
3. Remove the slot bracket from an available PCI-E slot
4. To install the board, carefully align the card's bus connector with the selected PCI-E slot on the motherboard. Push the board down firmly
5. Attach your internal devices to the SATA III (6Gbps) 2-port PCI-E Controller Card
6. Replace the slot bracket's holding screw to secure the card
7. Replace the computer cover and reconnect the power cord

Driver Installation

1. Please insert the CD driver into your CD ROM
2. Into the CD ROM (X:\Asmedia\1061)
3. Double click "setup"
4. Follow the on-screen instructions to complete the installation
5. Restart windows to complete the installation