

USB3.0 PCI-Express Controller Card

Data Transfer Rate up to 5.0Gb/s

User Manual

Ver. 1.00

All brand names and trademarks are properties of their respective owners

Features

- Compliant with the PCI Express Base Specification Revision 2.0
- Supports the PCI Bus Power Management Interface Specification Revision 1.2
- Compliant with the Universal Serial Bus 3.0 specification Revision 1.0
- Supports data rate : Super Speed(5 Gb/s), High Speed(480 Mb/s), Full Speed(12 Mb/s), Low Speed(1.5 Mb/s),
- Supports two USB3.0 ports
- Compliant with eXtensible Host Controller Interface (xHCI) , Specification revision 1.0
- Hot-swapping feature allows you to connect/disconnect devices without powering down the system

Package Contents

- 1 x USB3.0 PCI-Express Controller Card
- 1 x User Manual
- 1 x Driver CD

System Requirements:

Windows 7 / Vista / 2008 / 2003 / XP / 2000

Hardware Installation

1. Turn off the power to your computer.
2. Unplug the power cord and remove your computer's cover.
3. Remove the slot bracket from an available PCI-E slot.
4. To install the board, carefully align the card's bus connector with the selected PCI-E slot on the motherboard. Push the board down firmly.
5. Attach your internal devices to the PCI-E Ej168 card.
6. Replace the slot bracket's holding screw to secure the card.
7. Replace the computer cover and reconnect the power cord.

Driver Installation

1. Please insert the CD driver into your CD ROM.
2. Into the CD ROM (X: \ Etron \ EJ168)
3. Double click "setup"
4. Follow the on-screen instructions to complete the installation.
5. Restart windows to complete the installation.